

2/5/2013

**Slimline Thermoplastic LED Exit Sign**

**Features**

- Ultra-compact, low-profile design in neutral finish
- Energy-efficient LED technology
- EZ snap-out chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

**Electrical**

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED Board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**Electrical Information**

| Typical Performance | Red/Green     |     |
|---------------------|---------------|-----|
|                     | Input Voltage | 120 |
| Input Current (A)   | 0.9           | 0.9 |
| Input Power (W)     | 0.8           | 0.8 |

|              |  |
|--------------|--|
| Project:     |  |
| Catalog#:    |  |
| Approved by: |  |



**Illumination**

- Ultra-bright, energy efficient, long-lasting Red or Green LED.

**Housing**

- Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish
- Curved face, rounded corner design

**Mounting**

- Universal surface mount, wall or ceiling, with EZ-snap thermoplastic mounting canopy, which snaps into place making installation quick & easy.

**Dimensions**



**ORDERING INFORMATION**

| Model Family # | Operation                             | Number of Faces | Letter Color         | Housing Color          | Options                |
|----------------|---------------------------------------|-----------------|----------------------|------------------------|------------------------|
| HL0301         | Blank - AC Only<br>B - Battery Backup | 2 - Double Face | R - Red<br>G - Green | W - White<br>B - Black | RC - Remote Capability |

Example model# HL0301 B 2 R W

Specifications subject to change without notice.



Exit Sign