

2/7/2016

Exit/Emergency Combo

All LED Exit/Emergency Combo

Project:	
Catalog#:	
Approved by:	

Features

- Energy-efficient LED technology
- EZ snap-out chevron directional indicators
- Combines an EXIT sign & emergency light into one lowprofile unit
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-totest switch for mandated code compliance testing
- 9.6V, long-life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board & LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Catalog Number	Input Watts (W)		Input Amps (A)	
Catalog Number	120V	277V	120V	277V
HL0314 (Red Letters)	3.7	3.8	0.040	0.020
HL0314 (Green Letters) HL0314 (Green Letters) - RC	3.0	3.2	0.030	0.014
HL0314 (Red Letters) - RC	3.4	3.6	0.033	0.015
HL0314 (Red & Green) - SDT HL0314 (Red & Green) - RC - SDT	5.2	5.7	0.046	0.022

Illumination

- Long lasting, efficiency ultra-bright white LED lamp heads
- 1 watt (8 LEDs x 0.125 watt) per head
- High-performance smooth chrome plated metalized reflector and plastic lens for optimal light distribution
- Adjustable LED lamp heads provide optimal center-tocenter spacing. Optional high-lumen heads are available for increased center-to-center spacing.
- Long-life, energy efficient Red or Green LED exit sign illumination



Housing

- Injection-molded, engineering-grade, 5VA flame retardant, high-impact, thermoplastic in white or black finish
- EZ snap-out Chevron directional indicators

Mounting

- EZ-snap mounting canopy included for top or end mount
- Universal K/O patter on back plate for wall mount

21" 47/16" 12" 2" 2"

ORDERING INFORMATION							
Model Family #	Number of Faces	Letter Color	Housing Color	Options			
HL0314	3 - Universal	R - Red G - Green	B - Black W - White	RC - Remote Capable HL - High Lumen			
Example model# HL0314 3 R W							

Specifications subject to change without notice

