

3/22/2017

# High Bay Aluminum 16"

(Open Bottom Reflector)

PS / 400 watts | MH / 250-400 watts

### Applications

Ideal for lighting warehouses, industrial, and retail facilities

### Features

- Die-cast housing with electrical box (lamp included)
- Adjustable accessory bracket

**RAPID SHIP MODEL**  
**AVAILABLE FOR NEXT DAY SHIPMENT**

- HAL16O-400-PS-4T

### ORDERING INFORMATION

Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #	
HAL16O-400-PS-5T	400 PSMH	5T	PS-CWA	M155/O	MP400/BU/PS	<b>E</b>
HAL16O-400-PS-4T	400 PSMH	4T	PS-CWA	M155/O	MP400/BU/PS	*
HAL16O-400-PS-480	400 PS	480	PS-CWA	M155/O	MP400/BU/PS	*
HAL16O-250-MH-4T	250 MH	4T	CWA	M57/O	MP250/BU	*
HAL16O-400-MH-5T	400 MH	5T	CWA	M59/O	MP400/BU	*
HAL16O-400-MH-480	400 MH	480	CWA	M59/O	MP400/BU	*

### ACCESSORIES (sold separately)

Catalog #	Description	
16WG	Wire guard with stainless steel construction	*
QR	120v quartz restrike with socket, bracket, and dual contact bayonet (250 watt halogen lamp included)	*
HL	250 watt halogen lamp (fits 120v restrike socket and bracket)	*
SC	Insulated 3' steel safety cable with clear vinyl coating (includes a steel eye on one end and a loop on the opposite end)	*
SSH2	Malleable screw-shut hook	*
SPMRP	Swivel pendant mount round plate with a ball that allows the fixture to hang straight (mount to standard electrical box; fits 3/4" conduit)	*

**\*LIMITED QUANTITIES AVAILABLE**

† 4T = 120, 208, 240, 277 volts (pre-wired to 277)  
5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)  
480 = 480 volts

Specifications subject to change without notice.



Circle E logo indicates that this product complies with federal energy efficiency requirements.



Project:	
Catalog#:	
Approved by:	



### DIMENSIONS



### PHOTOMETRICS

