

3/22/2017

LIMITED QUANTITIES AVAILABLE

|              |  |
|--------------|--|
| Project:     |  |
| Catalog#:    |  |
| Approved by: |  |

# High Bay Aluminum 22"

(Enclosed - Glass Lens)

MH / 400 watts

### Applications

Ideal for lighting warehouses, industrial, and retail facilities

### Features

- Die-cast housing with electrical box (lamp included)
- Tempered glass lens
- Adjustable accessory bracket



HID/CFL Fixtures



### ORDERING INFORMATION

| Catalog #        | Watts  | Volts † | Ballast | ANSI  | Lamp Part # |
|------------------|--------|---------|---------|-------|-------------|
| HAL22E-400-MH-4T | 400 MH | 4T      | CWA     | M59/E | MH400/U     |
| HAL22E-400-MH-5T | 400 MH | 5T      | CWA     | M59/E | MH400/U     |

### ACCESSORIES (sold separately)


| Catalog # | Description   |
|-----------|---|
| 22WG      | Wire guard with stainless steel construction  |
| 22FG      | 22" flat glass  |
| 22CB      | 22" clamp band  |
| QR        | 120v quartz restrike with socket, bracket, and dual contact bayonet (250 watt halogen lamp included)  |
| HL        | 250 watt halogen lamp (fits 120v restrike socket and bracket)   |
| SC        | Insulated 3' steel safety cable with clear vinyl coating (includes a steel eye on one end and a loop on the opposite end)                   |
| SSH2      | Malleable screw-shut hook   |
| SPMRP     | Swivel pendent mount round plate with a ball that allows the fixture to hang straight (mount to standard electrical box; fits 3/4" conduit) |

### DIMENSIONS



### PHOTOMETRICS

400W MH @ 20' Mounting Height  
Isofootcandles



† 4T = 120, 208, 240, 277 volts (pre-wired to 277)  
5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)

Specifications subject to change without notice.

