

6/14/2017

Medium Wallpack

HPS / 70 - 150 watts | PS / 70 - 150 watts

Applications

Great for lighting parking facilities, entry ways, perimeters, pathways, and underpasses

Features

- Die-cast aluminum housing with hinged door frame (lamp included)
- Textured bronze finish with Borosilicate molded glass lens
- 1/2" conduit access, sides, top, or rear knockouts
- Photocell adaptable and UL listed for wet locations

**RAPID SHIP MODELS
AVAILABLE FOR NEXT DAY SHIPMENT**

- MWP-150-PS-4T

Project:	
Catalog#:	
Approved by:	



ORDERING INFORMATION					
Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
MWP-70-HPS-4T	70 HPS	4T	HX-HPF	S62	LU70/MED
MWP-150-HPS-4T	150 HPS	4T	HX-HPF	S55	LU150/55/MED
MWP-70-MH-4T	70 PSMH	4T	HX-HPF	M98/E	MH70/U/MED
MWP-100-MH-4T	100 PSMH	4T	HX-HPF	M90/E	MH100/U/MED
MWP-150-PS-4T	150 PSMH	4T	HX-HPF	M102/E	MH150/U/MED

ACCESSORIES (sold separately)	
Catalog #	Description
EPC-MV	External mount photocontrol - 120/208/240/277 multivolt
MWP-GF-100	Replacement glass lens and door frame
MWPPWG	Wire guard with stainless steel construction
MWPPSC	Side cutoff with textured bronze finish
MWPPVG	Clear polycarbonate vandal guard

***Limited Quantities Available**



† MV = 120-277 Universal Input
4T = 120, 208, 240, 277 volts (pre-wired to 277)

Circle E logo indicates that this product complies with federal energy efficiency requirements.



Specifications subject to change without notice.

DIMENSIONS



PHOTOMETRICS

150W PSMH @ 15' Mounting Height

